

NAVSEA
STANDARD ITEM

FY-03

ITEM NO: 009-92
DATE: 30 AUG 2001
CATEGORY: II

1. SCOPE:

1.1 Title: Resilient Mount; install

2. REFERENCES:

a. Standard Items

b. Equipment *Technical* Manual

c. S9073-A2-HBK-010, U.S. Navy Resilient Mount Handbook

3. REQUIREMENTS:

3.1 Notify the SUPERVISOR of the presence of heavily misloaded or deformed mounts prior to mount removal.

3.2 Remove resilient mount assemblies, using 2.b and 2.c for guidance.

3.2.1 Inspect each equipment foundation for structural integrity, deterioration, pitting, cracks, and areas of damage or distortion.

3.2.1.1 Submit four legible copies of a report listing the results of the requirements of 3.2.1 to the SUPERVISOR within 5 working days after equipment removal.

3.2.2 Accomplish the requirements of 009-32 of 2.a for each foundation of the removed assemblies.

3.3 Select, procure, assemble, install, load, and adjust new resilient mount assemblies including load bolts, foundation bolts, nuts, and snubbers in accordance with 2.c.

3.3.1 Stamp the installation date on each resilient mount flange adjacent to the identification date. The date shall be visible and legible when the mount is installed with 1/8-inch minimum lettering size.

3.3.2 Submit four legible copies of a report listing results of the requirements of 3.3 and 3.3.1 to the SUPERVISOR. The report shall include the following:

3.3.2.1 Ship's name and hull number

3.3.2.2 Contractor and subcontractor

3.3.2.3 Job Order and Work Item number

3.3.2.4 Identity of equipment

3.3.2.5 Amount and designation of mounts installed

4. NOTES:

4.1 Equipment **technical** manual and drawings referenced in invoking Work Item may identify mount designation and loading requirements.

4.2 Does not include SSDG and turbine enclosure mounts.